

# **Wambo Coal Mine and Rail Spur**

## **Environmental noise monitoring**

---

Prepared for Wambo Coal Pty Limited

March 2024

# Wambo Coal Mine and Rail Spur

## Environmental noise monitoring

Wambo Coal Pty Limited

E231300 RP3

March 2024

| Version | Date       | Prepared by    | Reviewed by  | Comments |
|---------|------------|----------------|--------------|----------|
| V1      | 04/04/2024 | Isaac Hepworth | Jesse Tribby | Final    |

Approved by



**Jesse Tribby**

Associate, Acoustics

4 April 2024

Level 3 175 Scott Street

Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Wambo Coal Pty Limited and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Wambo Coal Pty Limited's use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the Copyright Act 1968 (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Wambo Coal Pty Limited (and subject to the terms of EMM's agreement with Wambo Coal Pty Limited).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065. [2024]

# TABLE OF CONTENTS

---

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Introduction</b>                                    | <b>1</b>  |
| 1.1      | Background   | 1         |
| 1.2      | Attended monitoring locations                          | 1         |
| 1.3      | Terminology and abbreviations                          | 3         |
| <b>2</b> | <b>Noise limits</b>                                    | <b>4</b>  |
| 2.1      | Project approval                                       | 4         |
| 2.2      | WCM development consent                                | 4         |
| 2.3      | Environment protection licence                         | 4         |
| 2.4      | Noise management plan                                  | 4         |
| 2.5      | Noise limits   | 4         |
| 2.6      | Meteorological conditions                              | 5         |
| 2.7      | Additional requirements                                | 5         |
| 2.8      | Very noise-enhancing meteorological conditions         | 5         |
| <b>3</b> | <b>Methodology</b>                                     | <b>6</b>  |
| 3.1      | Overview   | 6         |
| 3.2      | Attended noise monitoring                              | 6         |
| 3.3      | Meteorological data                                    | 6         |
| 3.4      | Modifying factors                                      | 7         |
| 3.5      | Instrumentation and personnel                          | 7         |
| <b>4</b> | <b>Results</b>   | <b>8</b>  |
| 4.1      | Total measured noise levels and atmospheric conditions | 8         |
| 4.2      | Site-only noise levels                                 | 8         |
| <b>5</b> | <b>Discussion</b>                                      | <b>10</b> |
| 5.1      | Noted noise sources                                    | 10        |
| <b>6</b> | <b>Summary</b>   | <b>16</b> |

## Appendices

|            |                               |     |
|------------|-------------------------------|-----|
| Appendix A | Noise perception and examples | A.1 |
| Appendix B | Regulator documents           | B.1 |
| Appendix C | Calibration certificates      | C.1 |

## Tables

|           |   |     |
|-----------|---|-----|
| Table 1.1 | Attended noise monitoring locations                       | 1   |
| Table 1.2 | Terminology and abbreviations                             | 3   |
| Table 2.1 | Noise impact limits, dB                                   | 4   |
| Table 3.1 | Attended noise monitoring equipment                       | 7   |
| Table 4.1 | Total measured noise levels, dB – March 2024 <sup>1</sup> | 8   |
| Table 4.2 | Measured atmospheric conditions – March 2024              | 8   |
| Table 4.3 | Site noise levels and limits – March 2024                 | 9   |
| Table A.1 | Perceived change in noise                                 | A.2 |

## Figures

|            |  |     |
|------------|--|-----|
| Figure 1.1 | Attended noise monitoring locations                        | 2   |
| Figure 5.1 | Example graph (refer to Section 5.1 for explanatory note)  | 10  |
| Figure 5.2 | Environmental noise levels, N01 – Wambo Road               | 11  |
| Figure 5.3 | Environmental noise levels, N16 – Jerrys Plains Road       | 12  |
| Figure 5.4 | Environmental noise levels, N20A – Redmanvale Road Central | 13  |
| Figure 5.5 | Environmental noise levels, N21 – Wambo South              | 14  |
| Figure 5.6 | Environmental noise levels, N26 – Redmanvale Road South    | 15  |
| Figure A.1 | Common noise levels  | A.2 |

# 1 Introduction

## 1.1 Background

EMM Consulting Pty Ltd (EMM) was engaged by Wambo Coal Pty Limited to conduct a monthly noise survey of operations at Wambo Coal Mine (WCM, the site) and Wambo Coal Rail Spur (WCRS) located near Warkworth, NSW. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done at five monitoring locations during the night period of 6/7 March 2024.

## 1.2 Attended monitoring locations

Site monitoring locations are detailed in Table 1.1 and shown on Figure 1.1. It should be noted that Figure 1.1 shows actual monitoring positions, not necessarily the location of residences.

**Table 1.1** Attended noise monitoring locations

| Location descriptor | Description             | Coordinates (MGA56) |          |
|---------------------|-------------------------|---------------------|----------|
|                     |                         | Easting             | Northing |
| N01                 | North Bulga             | 313352              | 6388696  |
| N16                 | Jerrys Plains Road      | 306000              | 6399785  |
| N20A                | Redmanvale Road Central | 304461              | 6398713  |
| N21                 | South Wambo             | 310491              | 6390223  |
| N26                 | Redmanvale Road South   | 304172              | 6398160  |






Figure 1.1 Attended noise monitoring locations

### 1.3 Terminology and abbreviations

Some definitions of terms and abbreviations which may be used in this report are provided in Table 1.2.

**Table 1.2 Terminology and abbreviations**

| Term/descriptor         | Definition  |
|-------------------------|---|
| dB(A)                   | Noise level measurement units are decibels (dB). The “A” weighting scale is used to approximate how humans hear noise.  |
| L <sub>Amax</sub>       | The maximum root mean squared A-weighted noise level over a time period.  |
| L <sub>A1</sub>         | The A-weighted noise level which is exceeded for 1% of the time.  |
| L <sub>A1,1minute</sub> | The A-weighted noise level which is exceeded for 1% of the specified time period of 1 minute.   |
| L <sub>A10</sub>        | The A-weighted noise level which is exceeded for 10% of the time.   |
| L <sub>Aeq</sub>        | The energy average A-weighted noise level.  |
| L <sub>A50</sub>        | The A-weighted noise level which is exceeded for 50% of the time, also the median noise level during a measurement period.  |
| L <sub>A90</sub>        | The A-weighted noise level exceeded for 90% of the time, also referred to as the “background” noise level and commonly used to derive noise limits.   |
| L <sub>Amin</sub>       | The minimum A-weighted noise level over a time period.  |
| L <sub>Ceq</sub>        | The energy average C-weighted noise energy during a measurement period. The “C” weighting scale is used to take into account low-frequency components of noise within the audibility range of humans. |
| SPL                     | Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic scale, with the reference pressure being 20 micropascals.   |
| Hertz (Hz)              | The frequency of fluctuations in pressure, measured in cycles per second. Most sounds are a combination of many frequencies together.   |
| AWS                     | Automatic weather station used to collect meteorological data, typically at an altitude of 10 metres  |
| VTG                     | Vertical temperature gradient in degrees Celsius per 100 metres altitude.   |
| Sigma-theta             | The standard deviation of the horizontal wind direction over a period of time.  |
| IA                      | Inaudible. When site noise is noted as IA then there was no site noise at the monitoring location.  |
| NM                      | Not Measurable. If site noise is noted as NM, this means some noise was audible but could not be quantified.  |
| Day                     | Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.  |
| Evening                 | Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm.  |
| Night                   | Monday – Saturday: 10 pm to 7 am, on Sundays and Public Holidays: 10 pm to 8 am.  |
| WC                      | Wambo Coal  |
| WCM                     | Wambo Coal Mine   |
| WCRS                    | Wambo Coal Road Spur  |

Appendix A provides further information that gives an indication as to how an average person perceives changes in noise level, and examples of common noise levels.

## 2 Noise limits

### 2.1 Project approval

### 2.2 WCM development consent

The most current development consent for WCM is DA 305-7-2003 (MOD 19, 25 January 2023). Schedule 2, Part B and Appendix 5 of which detail specific conditions relating to noise generated by the site. Relevant WCM consent sections are reproduced in Appendix B.1.

#### 2.2.1 WCRS development consent

The most current development consent for Wambo Rail Loop is WCRS DA 177-8-2004 (MOD 3, 29 August 2019), last modified to include a rail refuelling facility. Schedule 2, Part B of which details specific conditions relating to noise generated by WCRS. Relevant WCRS consent sections are reproduced in Appendix B.2.

### 2.3 Environment protection licence

WCM holds Environment Protection Licence (EPL) No. 529 issued by the Environment Protection Authority (EPA), most recently on 30 September 2021. Relevant sections of the EPL are reproduced in Appendix B.3.

### 2.4 Noise management plan

Noise monitoring requirements are detailed in the Wambo Coal Noise Management Plan WA-ENV-MNP-503 (NMP; November 2020), prepared in accordance with the WCM and WCRS consents. Relevant sections of the NMP are reproduced in Appendix B.4.

### 2.5 Noise limits

Noise impact limits based on Phase 2 and 3 of the development consent (MOD 19) and the NMP are as shown in Table 2.1.

**Table 2.1** Noise impact limits, dB

| Location         | Day<br>$L_{Aeq,15minute}$ | Evening<br>$L_{Aeq,15minute}$ | Night<br>$L_{Aeq,15minute}$ | Night<br>$L_{A1,1minute}$ |
|------------------|---------------------------|-------------------------------|-----------------------------|---------------------------|
| N01 <sup>1</sup> | 38                        | 38                            | 38                          | 48                        |
| N16              | 35                        | 35                            | 35                          | 45                        |
| N20A             | 35                        | 35                            | 35                          | 45                        |
| N21 <sup>2</sup> | 39                        | 39                            | 39                          | 49                        |
| N26              | 35                        | 35                            | 35                          | 45                        |

Notes: 1. Noise criteria for the nearest privately-owned property (R003) have been adopted.

2. Noise criteria for the nearest privately-owned property (R025) have been adopted.

EPL noise limits have not been updated for Phase 2 and 3 of operations. As limits in the development consent and NMP are now more conservative than those in the EPL they have been adopted in Table 2.1.



## 2.6 Meteorological conditions

Appendix 5 of MOD 19 details specific meteorological conditions required for noise limits to be applicable:

### APPENDIX 5 NOISE COMPLIANCE ASSESSMENT

#### Applicable Meteorological Conditions

1. The noise criteria in condition B12 are to apply under all meteorological conditions except the following:
  - (a) where 3°C/100 metres (m) lapse rates have been assessed, then:
    - (i) wind speeds greater than 3 metres/second (m/s) measured at 10m above ground level;
    - (ii) temperature inversion conditions between 1.5°C and 3°C/100m and wind speeds greater than 2m/s measured at 10m above ground level; or
    - (iii) temperature inversion conditions greater than 3°C/100m.
  - (b) where Pasquill Stability Classes have been assessed, then:
    - (i) wind speeds greater than 3m/s at 10m above ground level;
    - (ii) stability category F temperature inversion conditions and wind speeds greater than 2m/s at 10m above ground level;
    - (iii) stability category G temperature inversion conditions.

As lapse rates (VTG) were not measured directly, meteorological conditions have been assessed against requirements detailed in 1.(b), which are consistent with the EPL.

## 2.7 Additional requirements

Monitoring and reporting have been done in accordance with the NSW EPA 'Noise Policy for Industry' (NPfI) issued in October 2017 and the 'Approved methods for the measurement and analysis of environmental noise in NSW' (Approved Methods) issued in January 2022.

## 2.8 Very noise-enhancing meteorological conditions

In accordance with the Approved Methods, monthly noise monitoring for the site is scheduled to occur during forecasted meteorological conditions where noise limits in Table 2.1 will be applicable. However, in cases where actual meteorological conditions do not align with forecasts and noise limits are subsequently not directly applicable, it is the expectation of regulators that noise impact still be managed.

The NPfI states that:

Noise limits derived for consents and licences will apply under the meteorological conditions used in the environmental assessment process, that is, standard or noise-enhancing meteorological conditions. For 'very noise-enhancing meteorological conditions' ... a limit is set based on the limit derived under standard or noise-enhancing conditions (whichever is adopted in the assessment) plus 5 dB. In this way a development is subject to noise limits under all meteorological conditions.

Therefore, if monthly noise monitoring occurs during meteorological conditions outside of those specified in Section 2.6, site limits will be adjusted based on Table 2.1 plus 5 dB.

## 3 Methodology

### 3.1 Overview

Attended environmental noise monitoring was done in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant NSW EPA requirements.

### 3.2 Attended noise monitoring

During this survey, attended noise monitoring was conducted during the night period at each location. The duration of each measurement was 15 minutes. Atmospheric conditions were measured at each monitoring location.

Measured sound levels from various sources were noted during each measurement, and particular attention was paid to the extent of site's contribution (if any) to measured levels. At each monitoring location, the site-only  $L_{Aeq,15minute}$  and  $L_{Amax}$  were measured directly or determined by other methods detailed in Section 7.1 of the NPfI.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may be used in this report. When site noise is noted as IA, it was inaudible at the monitoring location. When site noise is noted as NM, this means it was audible but could not be quantified. All results noted as IA or NM in this report were due to one or more of the following:

- Site noise levels were very low, typically more than 10 dB below the measured background ( $L_{A90}$ ), and unlikely to be noticed.
- Site noise levels were masked by more dominant sources that are characteristic of the environment (such as breeze in foliage or continuous road traffic noise) that cannot be eliminated by monitoring at an alternate or intermediate location.
- It was not feasible or reasonable to employ methods such as move closer and back calculate. Cases may include rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and meteorological conditions where back calculation may not be accurate.

If exact noise levels from site could not be established due to masking by other noise sources in a similar frequency range but were determined to be at least 5 dB lower than relevant limits, then a maximum estimate of site noise may be provided. This is expressed as a 'less than' quantity, such as <20 dB or <30 dB.

For this assessment, the measured  $L_{Amax}$  has been used as a conservative estimate of  $L_{A1,1minute}$ . The EPA accepts sleep disturbance analysis based on either the  $L_{A1,1minute}$  or  $L_{Amax}$  metrics, with the  $L_{Amax}$  representing a more conservative assessment of site noise emissions.

### 3.3 Meteorological data

Meteorological data was obtained from the WCM automated weather station (AWS) which allowed correlation of atmospheric parameters with measured noise levels. This data was logged at 10-minute intervals. Atmospheric parameters include wind speed, wind direction, rainfall, and sigma theta. When meteorological data is provided in less than 15-minute intervals, analysis must be conducted to determine the meteorological conditions present for the majority of each measurement period and whether those conditions result in noise criteria being applicable or not.

### 3.4 Modifying factors

All measurements were evaluated for potential modifying factors in accordance with the NPfl at the time of measurement. If applicable, modifying factor penalties have been reported and added to measured site-only  $L_{Aeq}$  noise levels.

Low-frequency modifying factor penalties have only been applied to site-only  $L_{Aeq}$  if the site was the only contributing low-frequency noise source. Specific methodology for assessment of each modifying factor is outlined in Fact Sheet C of the NPfl.

### 3.5 Instrumentation and personnel

Attended noise monitoring was conducted by Rob Kirwan and Ryan Bruniges. Qualifications, experience, and/or demonstration of competence in accordance with the Approved methods is available upon request.

Equipment used to measure environmental noise levels is detailed in Table 3.1. Calibration certificates are provided in Appendix C.

**Table 3.1** Attended noise monitoring equipment

| Item                            | Serial number | Calibration due date | Relevant standard |
|---------------------------------|---------------|----------------------|-------------------|
| Rion NA-28 sound level meter    | 00701424      | 01/06/2025           | IEC 61672-1:2002  |
| Rion NA-28 sound level meter    | 30131882      | 23/01/2025           | IEC 61672-1:2002  |
| Svante SV36 acoustic calibrator | 140737        | 06/09/2025           | IEC 60942:2003    |
| Pulsar 106 acoustic calibrator  | 81334         | 21/06/2025           | IEC 60942:2003    |

## 4 Results

### 4.1 Total measured noise levels and atmospheric conditions

Total noise levels measured during each 15-minute attended measurement are provided in Table 4.1. Discussion as to the sources responsible for total is provided in Section 5 of this report.

**Table 4.1** Total measured noise levels, dB – March 2024 <sup>1</sup>

| Location | Start date and time | L <sub>Amax</sub> | L <sub>A1</sub> | L <sub>A10</sub> | L <sub>Aeq</sub> | L <sub>A50</sub> | L <sub>A90</sub> | L <sub>Amin</sub> |
|----------|---------------------|-------------------|-----------------|------------------|------------------|------------------|------------------|-------------------|
| N01      | 7/03/2024 00:30     | 51                | 41              | 37               | 35               | 35               | 34               | 32                |
| N16      | 6/03/2024 23:36     | 45                | 38              | 36               | 34               | 34               | 32               | 29                |
| N20A     | 6/03/2024 22:39     | 48                | 38              | 35               | 33               | 32               | 30               | 28                |
| N21      | 7/03/2024 00:01     | 40                | 39              | 38               | 36               | 35               | 33               | 31                |
| N26      | 6/03/2024 22:07     | 40                | 36              | 35               | 34               | 33               | 32               | 31                |

Notes: 1. Levels in this table are not necessarily the result of activity at site.

Atmospheric condition data measured by the operator during each measurement using a hand-held weather meter is shown in Table 4.2. The wind speed, direction and temperature were measured at approximately 1.5 metres. Attended noise monitoring is not done during rain, hail, or wind speeds above 5 m/s at microphone height.

**Table 4.2** Measured atmospheric conditions – March 2024

| Location | Start date and time | Temperature °C | Wind speed m/s | Wind direction ° magnetic north <sup>1</sup> | Cloud cover 1/8s |
|----------|---------------------|----------------|----------------|--|------------------|
| N01      | 7/03/2024 00:30     | 22             | <0.5           | -  | 0                |
| N16      | 6/03/2024 23:36     | 27             | <0.5           | 200  | 2                |
| N20A     | 6/03/2024 22:39     | 27             | <0.5           | -  | 0                |
| N21      | 7/03/2024 00:01     | 24             | <0.5           | -  | 0                |
| N26      | 6/03/2024 22:07     | 26             | <0.5           | -  | 1                |

Notes: 1. "-" indicates calm conditions at monitoring location.

### 4.2 Site-only noise levels

#### 4.2.1 Modifying factors

There were no modifying factors, as defined in the NPfI, applicable during the survey.

## 4.2.2 Monitoring results

Table 4.3 provides site noise levels in the absence of other sources, where possible, and includes weather data from the site AWS. Noise limits are applicable under all weather conditions but are adjusted during very noise-enhancing meteorological conditions as defined by the NPfI.

**Table 4.3 Site noise levels and limits – March 2024**

| Location | Start date and time | Wind      |                        | Stability class | Very enhancing? <sup>1</sup> | Limits, dB                |                   | Site levels, dB <sup>2</sup> |                   | Exceedances, dB           |                   |
|----------|---------------------|-----------|------------------------|-----------------|------------------------------|---------------------------|-------------------|------------------------------|-------------------|---------------------------|-------------------|
|          |                     | Speed m/s | Direction <sup>3</sup> |                 |                              | L <sub>Aeq,15minute</sub> | L <sub>Amax</sub> | L <sub>Aeq,15minute</sub>    | L <sub>Amax</sub> | L <sub>Aeq,15minute</sub> | L <sub>Amax</sub> |
| N01      | 7/03/2024 00:30     | 0.8       | 90                     | F               | No                           | 38                        | 48                | IA                           | IA                | Nil                       | Nil               |
| N16      | 6/03/2024 23:36     | 1.4       | 88                     | D               | No                           | 35                        | 45                | IA                           | IA                | Nil                       | Nil               |
| N20A     | 6/03/2024 22:39     | 1.0       | 77                     | F               | No                           | 35                        | 45                | IA                           | IA                | Nil                       | Nil               |
| N21      | 7/03/2024 00:01     | 0.9       | 92                     | F               | No                           | 39                        | 49                | IA                           | IA                | Nil                       | Nil               |
| N26      | 6/03/2024 22:07     | 0.7       | 129                    | F               | No                           | 35                        | 45                | IA                           | IA                | Nil                       | Nil               |

- Notes:
1. Noise limits are adjusted by +5 dB during 'very enhancing meteorological conditions' in accordance with the NPfI.
  2. Site-only L<sub>Aeq,15minute</sub> includes modifying factor penalties if applicable.
  3. Degrees magnetic north, "-" indicates calm conditions.

# 5 Discussion

## 5.1 Noted noise sources

During attended monitoring, the time variations (temporal characteristics) of noise sources are considered in each measurement via statistical descriptors. From these observations, summaries have been derived for the location and provided in this chapter. Statistical 1/3 octave-band analysis of environmental noise was undertaken, and the following figures display frequency ranges of various noise sources at each location for  $L_{A1}$ ,  $L_{A10}$ ,  $L_{Aeq}$ ,  $L_{A50}$ , and  $L_{A90}$  descriptors. These figures also provide, graphically, statistical information for these noise levels.

An example is provided as Figure 5.1, where frogs and insects are seen to be generating noise at frequencies above 1,000 Hz, while industrial noise is observed at frequencies less than 1,000 Hz.





Figure 5.1 Example graph (refer to Section 5.1 for explanatory note)



5.1.1 N01




**Figure 5.2 Environmental noise levels, N01 – Wambo Road**

WCM was inaudible during the measurement.

Frogs, insects, and continuum from another mining operation generated total measured levels.

5.1.2 N16




**Figure 5.3 Environmental noise levels, N16 – Jerrys Plains Road**

WCM was inaudible during the measurement.

Continuum from another mining operation, frogs, and insects generated total measured levels.

Noise from road traffic tyres was also noted.

5.1.3 N20A




**Figure 5.4 Environmental noise levels, N20A – Redmanvale Road Central**

WCM was inaudible during the measurement.

Continuum from another mining operation generated total measured levels.

Noise from road traffic tyres was also noted.

5.1.4 N21




**Figure 5.5 Environmental noise levels, N21 – Wambo South**

WCM was inaudible during the measurement.

Frogs, insects, and continuum from another mining operation generated total measured levels.

Noise from birds and aircraft was also noted.



**Figure 5.6 Environmental noise levels, N26 – Redmanvale Road South**

WCM was inaudible during the measurement.

Continuum from another mining operation was primarily responsible for total measured levels. Insects contributed to the measured  $L_{Aeq}$ ,  $L_{A50}$ , and  $L_{A90}$ .

Continuum from local irrigation was also noted.

## 6 Summary

EMM was engaged by Wambo Coal Pty Limited to conduct a monthly noise survey of operations at WCM and WCRS. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done at five monitoring locations during the night period of 6/7 March 2024.

Noise levels from site complied with relevant limits at all monitoring locations during the March 2024 survey.



---

# Appendix A

## Noise perception and examples


---

## A.1 Noise levels

Table A.1 gives an indication as to how an average person perceives changes in noise level. Examples of common noise levels are provided in Figure A.1.

**Table A.1 Perceived change in noise**

| Change in sound pressure level (dB) | Perceived change in noise       |
|-------------------------------------|---------------------------------|
| Up to 2                             | Not perceptible                 |
| 3                                   | Just perceptible                |
| 5                                   | Noticeable difference           |
| 10                                  | Twice (or half) as loud         |
| 15                                  | Large change                    |
| 20                                  | Four times (or quarter) as loud |



**Figure A.1 Common noise levels**

---

# Appendix B

## Regulator documents

---

## B.1 Wambo Coal Mine development consent

### NOISE

#### Operational Noise Criteria

- B12. During Phase 1, the Applicant must ensure that the noise generated by the Wambo Mining Complex does not exceed the criteria in Table 3 at any residence<sup>a</sup> on privately-owned land.

**Table 3:** Operational noise criteria dB(A) for Phase 1

| Noise Assessment Location            | Day<br><i>L<sub>Aeq</sub></i> (15 min) | Evening/Night<br><i>L<sub>Aeq</sub></i> (15 min) | Night<br><i>L<sub>A1</sub></i> (1 min) |
|--------------------------------------|--|--|--|
| R016                                 | 40                                     | 40   | 50                                     |
| R025                                 |  |  |  |
| R029                                 |  |  |  |
| R033                                 |  |  |  |
| R320 (previously 15B)                |  |  |  |
| R345 (previously 15B)                |  |  |  |
| R006                                 | 39                                     | 39   | 50                                     |
| R007                                 |  |  |  |
| R048                                 |  |  |  |
| R343 (previously 37)                 |  |  |  |
| R030 (previously 38)                 | 38                                     | 38   | 50                                     |
| R049                                 |  |  |  |
| R075                                 |  |  |  |
| R346                                 |  |  |  |
| R348                                 |  |  |  |
| R163                                 | 37                                     | 37   | 50                                     |
| R344 (previously 137)                |  |  |  |
| All other privately-owned residences | 35                                     | 35   | 50                                     |

<sup>a</sup> The Noise Assessment Locations referred to in Table 3 are shown in Appendix 4.

- B13. During Phase 2 and Phase 3, the Applicant must ensure that the noise generated by the Wambo Mining Complex does not exceed the criteria in Table 4 at any residence<sup>a</sup> on privately-owned land.

**Table 4:** Operational noise criteria dB(A) for Phase 2 and Phase 3

| Noise Assessment Area      | Noise Assessment Location            | Day<br><i>L<sub>Aeq</sub></i> (15 min) | Evening<br><i>L<sub>Aeq</sub></i> (15 min) | Night<br><i>L<sub>Aeq</sub></i> (15 min) | Night<br><i>L<sub>A1</sub></i> (1 min) |
|----------------------------|--------------------------------------|--|--|--|--|
| Area 1 - North Bulga       | R007                                 | 37                                     | 37   | 37                                       | 47                                     |
|                            | All other privately-owned residences | 35                                     | 35   | 35                                       | 45                                     |
| Area 2 - South Wambo       | R025                                 | 39                                     | 39   | 39                                       | 49                                     |
|                            | All other privately-owned residences | 35                                     | 35   | 35                                       | 45                                     |
| Area 3 - Warkworth Village | All other privately-owned residences | 44                                     | 44   | 43                                       | 53                                     |
| All other areas            | All privately-owned residences       | 35                                     | 35   | 35                                       | 45                                     |

<sup>a</sup> The Noise Assessment Areas referred to in Table 4 are shown in Appendix 4.

- B14. Noise generated by the Wambo Mining Complex must be measured in accordance with the relevant requirements and exemptions (including certain meteorological conditions) of the *NSW Industrial Noise Policy* (EPA, 2000). Appendix 5 of this consent sets out the meteorological conditions under which these criteria apply and the requirements for evaluating compliance with these criteria.
- B15. The noise criteria in Table 3 and Table 4 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

### Noise Operating Conditions

B16. The Applicant must:

- (a) take all reasonable steps to minimise all noise from construction and operational activities, including low frequency and other audible characteristics, as well as road noise associated with the development;
- (b) monitor and record all major equipment use and make this data readily available at the request of the Department or the EPA;
- (c) operate a noise management system commensurate with the risk of impact to ensure compliance with the relevant conditions of this consent;
- (d) take all reasonable steps to minimise the noise impacts of the development during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see Appendix 5); and
- (e) carry out regular attended noise monitoring (at least once a month, unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent.

### Noise Management Plan

B17. The Applicant must prepare a Noise Management Plan for the Wambo Mining Complex to the satisfaction of the Planning Secretary. This plan must:

- (a) be prepared by a suitably qualified and experienced person/s;
- (b) be prepared in consultation with the EPA;
- (c) describe the measures to be implemented to ensure:
  - (i) compliance with the noise criteria and operating conditions in this consent;
  - (ii) best practice management is being employed; and
  - (iii) noise impacts of the development are minimised during noise-enhancing meteorological conditions under which the noise criteria in this consent do not apply (see Appendix 5);
- (d) seek to minimise road traffic noise generated by employee commuter vehicles on public roads;
- (e) describe the noise management system in detail; and
- (f) include a monitoring program that:
  - (i) uses a combination of real-time and supplementary attended monitoring to evaluate the performance of the development;
  - (ii) includes a program to calibrate and validate the real-time noise monitoring results with the attended monitoring results over time;
  - (iii) adequately supports the noise management system; and
  - (iv) includes a protocol for distinguishing noise emissions between the Wambo Mining Complex and United Wambo open cut coal mine; and
  - (v) includes a protocol for identifying any noise-related exceedance, incident or non-compliance and for notifying the Department and relevant stakeholders of any such event.

B18. The Applicant must not commence Phase 2 until the Noise Management Plan is approved by the Planning Secretary.

B19. The Applicant must implement the Noise Management Plan as approved by the Planning Secretary.

## APPENDIX 5 NOISE COMPLIANCE ASSESSMENT

### Applicable Meteorological Conditions

1. The noise criteria in condition B12 are to apply under all meteorological conditions except the following:
  - (a) where 3°C/100 metres (m) lapse rates have been assessed, then:
    - (i) wind speeds greater than 3 metres/second (m/s) measured at 10m above ground level;
    - (ii) temperature inversion conditions between 1.5°C and 3°C/100m and wind speeds greater than 2m/s measured at 10m above ground level; or
    - (iii) temperature inversion conditions greater than 3°C/100m.
  - (b) where Pasquill Stability Classes have been assessed, then:
    - (i) wind speeds greater than 3m/s at 10m above ground level;
    - (ii) stability category F temperature inversion conditions and wind speeds greater than 2m/s at 10m above ground level;
    - (iii) stability category G temperature inversion conditions.

### Determination of Meteorological Conditions

2. Except for wind speed at microphone height, the data to be used for determining meteorological conditions shall be that recorded by the meteorological station required under condition B50.

### Compliance Monitoring

3. Unless otherwise agreed by the Planning Secretary, this monitoring must be carried out in accordance with the relevant requirements for reviewing performance set out in the *NSW Industrial Noise Policy* (EPA, 2000), in particular the requirements relating to:
  - (a) monitoring locations for the collection of representative noise data;
  - (b) meteorological conditions during which collection of noise data is not appropriate;
  - (c) equipment used to collect noise data, and conformity with Australian Standards relevant to such equipment; and
  - (d) modifications to noise data collected, including for the exclusion of extraneous noise and/or penalties for modifying factors apart from adjustments for duration,

with the exception of applying appropriate modifying factors for low frequency noise during compliance testing. This should be undertaken in accordance with Fact Sheet C of the *NSW Noise Policy for Industry* (EPA, 2017).



## B.2 Wambo Rail Spur development consent

### PART B SPECIFIC ENVIRONMENTAL CONDITIONS

#### NOISE

##### Noise Operating Conditions

- B1. The Applicant must:
- (a) take all reasonable steps to minimise all noise associated with the development, including during noise-enhancing meteorological conditions;
  - (b) operate a noise management system commensurate with the risk of impact to ensure compliance with the relevant conditions of this consent;
  - (c) only use locomotives and rolling stock that are approved to operate on the NSW rail network in accordance with the noise limits in ARTC's EPL and use reasonable endeavours to ensure that rolling stock is selected to minimise noise;
  - (d) use all reasonable efforts to co-ordinate noise management on the site with the noise management at Wambo mine; and
  - (e) carry out regular attended noise monitoring to determine whether the development is complying with the relevant conditions of this consent.

## B.3 Environmental protection licence

### L5 Noise limits

L5.1 Noise generated at the premises must not exceed the noise limits presented in the table below. The noise limits in the table below represent the noise contribution from the premises.

| Receiver Land Number                 | Day LAeq(15 minute) | Evening LAeq(15 minute) | Night LAeq(15 minute) | Night LA1(1 minute) |
|--------------------------------------|---------------------|-------------------------|-----------------------|---------------------|
| EPA Point 20 in NMG1                 | 40                  | 40                      | 40                    | 50                  |
| EPA Point 21 in NMG2                 | 40                  | 40                      | 40                    | 50                  |
| EPA Point 22 in NMG3                 | 40                  | 40                      | 40                    | 50                  |
| EPA Point 23 in NMG4                 | 38                  | 38                      | 38                    | 50                  |
| Residence 019                        | 59                  | 59                      | 59                    |                     |
| Residence 003 and 025 in NMG3        | 40                  | 40                      | 40                    | 50                  |
| Residence 016 and 039 in NMG1        | 40                  | 40                      | 40                    | 50                  |
| Residence 029, 042 and 345 in NMG4   | 40                  | 40                      | 40                    | 50                  |
| Residence 033 and 320 in NMG2        | 40                  | 40                      | 40                    | 50                  |
| Residence 006 and 007 in NMG3        | 39                  | 39                      | 39                    | 50                  |
| Residence 048 and 343                | 39                  | 39                      | 39                    | 50                  |
| Residence 017 in NMG1                | 38                  | 38                      | 38                    | 50                  |
| Residence 030, 035, 049, 075 and 379 | 38                  | 38                      | 38                    | 50                  |
| Residence 346 and 348 in NMG4        | 38                  | 38                      | 38                    | 50                  |
| Residence 344 in NMG2                | 37                  | 37                      | 37                    | 50                  |
| Residence 043, 163, 380 and 381      | 37                  | 37                      | 37                    | 50                  |

|  |    |    |    |    |
|--|----|----|----|----|
| All other privately owned residences in Appendix 4 of DA 305-7-2003 29 August 2019 | 35 | 35 | 35 | 50 |
|--|----|----|----|----|

- L5.2 For the purpose of Condition L5.1:
- Day is defined as the period from 7am to 6pm Monday to Saturday and 8am to 6pm Sundays and Public Holidays;
  - Evening is defined as the period from 6pm to 10pm; and
  - Night is defined as the period from 10pm to 7am Monday to Saturday and 10pm to 8am Sundays and Public Holidays.
- L5.3 The noise limits set out in condition L5.1 apply under all meteorological conditions except for the following:
- Wind speeds greater than 3 metres/second at 10 metres above the ground level;
  - Stability category F temperature inversion conditions and wind speeds greater than 2 metres/second at 10 metres above ground level; or
  - Stability category G temperature inversion conditions.
- L5.4 For the purposes of condition L5.5:
- Data recorded by the closest and most representative meteorological station installed on the premises at EPA Identification Point 17 must be used to determine meteorological conditions; and
  - Temperature inversion conditions (stability category) are to be determined by the methods referred to in Fact Sheet D of the Noise Policy for Industry (2017).

Note: For the purposes of condition L5.1:

- Noise receiver locations and associated noise limits are defined in Appendix 4 of development consent DA 305-7-2003 dated 29 August 2019 at EPA reference: DOC19/1117963.
- Noise monitoring groups (NMG) are defined in the document titled '*Wambo Coal Mine Noise Monitoring Groups Noise Modelling Evaluation*' dated 16 August 2019 at EPA reference DOC19/704212.

## 5.0 Noise Monitoring Program

### 5.1 Attended Noise Monitoring

WCPL attended noise monitoring is carried out monthly. The monitoring is conducted by a WCPL appointed acoustic specialist who measures and describes the acoustic environment at each attended monitoring location. The attended noise monitoring results are compared with noise impact assessment criteria (as defined in Section 3.1) to assess compliance. Attended noise monitoring is considered the preferred method for determining compliance with prescribed limits because it allows for an accurate determination of the contribution, if any, made by industrial noise sources to measured ambient noise levels.

Operator attended noise measurements are conducted during night period<sup>3</sup> operations to quantify noise emissions from WCPL as well as the overall level of ambient noise.

Noise levels ( $LA_{max}$  and  $LA_{eq}$ ) from the Mine are quantified over a 15 minute measurement period. In addition, the overall levels of ambient noise (i.e.  $LA_{max}$ ,  $LA_{1}$ ,  $LA_{10}$ ,  $LA_{50}$ ,  $LA_{50}$ , and  $LA_{eq}$ ) over the 15 minute period will be quantified and characterised.

Attended noise monitoring will be conducted at a representative location in accordance with the NPfI and Australian Standard AS 1055 'Acoustics, Description and Measurement of Environmental Noise'.

Attended noise monitoring is undertaken at five locations as shown in Table 5. The attended noise monitoring network locations have been strategically chosen to provide sufficiently appropriate noise monitoring coverage (refer to Figure 5).

Table 5: Attended Noise Monitoring Locations

| Noise Assessment Area* | Site Ref | EPL529 ID | Description             | Approximate Co-ordinates (MGA 94, z56) |          | Representative Addresses                       |
|------------------------|----------|-----------|-------------------------|--|----------|--|
|                        |          |           |                         | Easting                                | Northing |  |
| 1                      | N01      | N/A       | North Bulga             | 313352                                 | 6388696  | 3, 7, 379                                      |
| 2                      | N21      | 22        | South Wambo             | 310586                                 | 6390149  | 25, 35a  |
| -                      | N16      | 20        | Jerrys Plains Road      | 308000                                 | 6399785  | Privately owned residences near Jerry's Plains |
| -                      | N20A     | 21        | Redmanvale Road Central | 304666                                 | 6399100  | Privately owned residences near Jerry's Plains |
| -                      | N26      | 23        | Redmanvale Road South   | 304172                                 | 6398160  | Privately owned residences near Jerry's Plains |

Notes for Table 5

\* The Noise Assessment Areas are shown on Figure 5

<sup>3</sup>In general, weather enhancing conditions are more likely to occur at night which has the greatest potential to cause an exceedance. This approach is consistent with the NSW Draft Guidelines: Mining Noise Monitoring Application Note. However WCPL will review the data in accordance with this Noise Management Plan to determine if there are compelling reasons to revert back to day time attended monitoring. Please note that evening and night time noise level criteria are the same.

Measurement of rail pass-by noise levels was removed from the monitoring program in Version 5 of the NMP, following a demonstrated history of compliance. Monitoring will be recommenced if triggered by complaint or change in rolling stock used to transport coal from WCPL.

Meteorological data from the WCPL meteorological station will be utilised to correlate atmospheric parameters and measured noise levels. Ground level atmospheric condition measurement is also undertaken during attended monitoring. Noise criteria only apply in meteorological conditions specified in the conditions. A detailed Compliance Assessment Methodology has been developed to determine the individual noise contributions of the separate United Wambo and Wambo operations (Section 6.1).

Modifying factors will be assessed in accordance with the NPfI.

---

# Appendix C

## Calibration certificates

---

C.1 Calibration certificates



**Sound Level Meter**  
IEC 61672-3:2013  
**Calibration Certificate**  
Calibration Number C23032

|  |  |
|--|--|
| <b>Client Details</b>                        | EMM Consulting<br>Level 3/175 Scott Street<br>Newcastle NSW 2300 |
| <b>Equipment Tested/ Model Number :</b>      | Rion NA-28   |
| <b>Instrument Serial Number :</b>            | 30131882   |
| <b>Microphone Serial Number :</b>            | 04739  |
| <b>Pre-amplifier Serial Number :</b>         | 11942  |
| <b>Firmware Version :</b>                    | 2.0  |
| <b>Pre-Test Atmospheric Conditions</b>       | <b>Post-Test Atmospheric Conditions</b>                          |
| Ambient Temperature : 24°C                   | Ambient Temperature : 23.5°C                                     |
| Relative Humidity : 47.3%                    | Relative Humidity : 46.1%  |
| Barometric Pressure : 100.14kPa              | Barometric Pressure : 100.16kPa                                  |
| <b>Calibration Technician :</b> Shaheen Boaz | <b>Secondary Check:</b> Dylan Selge                              |
| <b>Calibration Date :</b> 23 Jan 2023        | <b>Report Issue Date :</b> 25 Jan 2023                           |
| <b>Approved Signatory :</b>                  | Ken Williams   |

| Clause and Characteristic Tested                   | Result | Clause and Characteristic Tested                  | Result |
|--|--------|---|--------|
| 12: Acoustical Sig. tests of a frequency weighting | Pass   | 17: Level linearity incl. the level range control | Pass   |
| 13: Electrical Sig. tests of frequency weightings  | Pass   | 18: Toneburst response                            | Pass   |
| 14: Frequency and time weightings at 1 kHz         | Pass   | 19: C Weighted Peak Sound Level                   | Pass   |
| 15: Long Term Stability                            | Pass   | 20: Overload Indication                           | Pass   |
| 16: Level linearity on the reference level range   | Pass   | 21: High Level Stability                          | Pass   |

The sound level meter submitted for testing has successfully completed the class 1 periodic tests of IEC 61672-3:2013, for the environmental conditions under which the tests were performed.

However, no general statement or conclusion can be made about conformance of the sound level meter to the full requirements of IEC 61672-1:2013 because evidence was not publicly available, from an independent testing organisation responsible for pattern approvals, to demonstrate that the model of sound level meter fully conformed to the requirements in IEC 61672-1:2013 and because the periodic tests of IEC 61672-3:2013 cover only a limited subset of the specifications in IEC 61672-1:2013.

| Uncertainties of Measurement - |         |                          |           |
|--------------------------------|---------|--------------------------|-----------|
| Acoustic Tests                 |         | Environmental Conditions |           |
| 125Hz                          | ±0.13dB | Temperature              | ±0.1°C    |
| 1kHz                           | ±0.13dB | Relative Humidity        | ±1.9%     |
| 8kHz                           | ±0.14dB | Barometric Pressure      | ±0.014kPa |
| Electrical Tests               | ±0.13dB |                          |           |

*All uncertainties are derived at the 95% confidence level with a coverage factor of 2.*



This calibration certificate is to be read in conjunction with the calibration test report.

Acoustic Research Labs Pty Ltd is NATA Accredited Laboratory Number 14172. Accredited for compliance with ISO/IEC 17025 - Calibration.

The results of the tests, calibrations and/or measurements included in this document are traceable to SI units.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports.



**Acoustic  
Research  
Labs Pty Ltd**

Unit 36/14 Loyalty Rd  
North Rocks NSW AUSTRALIA 2151  
Ph: +61 2 9484 0800 A.B.N. 65 160 399 119  
www.acousticresearch.com.au

## Sound Level Meter IEC 61672-3:2013 Calibration Certificate

Calibration Number C23317

|   |   |
|---|---|
| <b>Client Details</b>                     | EMM Consulting<br>Level 3, 175 Scott Street<br>Newcastle NSW 2300 |
| <b>Equipment Tested/ Model Number :</b>   | NA-28   |
| <b>Instrument Serial Number :</b>         | 00701424  |
| <b>Microphone Serial Number :</b>         | 01916   |
| <b>Pre-amplifier Serial Number :</b>      | 01463   |
| <b>Firmware Version :</b>                 | 2.0   |
| <b>Pre-Test Atmospheric Conditions</b>    | <b>Post-Test Atmospheric Conditions</b>                           |
| <b>Ambient Temperature :</b> 24°C         | <b>Ambient Temperature :</b> 22.6°C                               |
| <b>Relative Humidity :</b> 46%            | <b>Relative Humidity :</b> 46.6%                                  |
| <b>Barometric Pressure :</b> 100.6kPa     | <b>Barometric Pressure :</b> 100.6kPa                             |
| <b>Calibration Technician :</b> Max Moore | <b>Secondary Check:</b> Dylan Selge                               |
| <b>Calibration Date :</b> 1 Jun 2023      | <b>Report Issue Date :</b> 2 Jun 2023                             |
| <b>Approved Signatory :</b>               | Ken Williams  |

| Clause and Characteristic Tested                   | Result | Clause and Characteristic Tested                  | Result |
|--|--------|---|--------|
| 12: Acoustical Sig. tests of a frequency weighting | Pass   | 17: Level linearity incl. the level range control | Pass   |
| 13: Electrical Sig. tests of frequency weightings  | Pass   | 18: Toneburst response                            | Pass   |
| 14: Frequency and time weightings at 1 kHz         | Pass   | 19: C Weighted Peak Sound Level                   | Pass   |
| 15: Long Term Stability                            | Pass   | 20: Overload Indication                           | Pass   |
| 16: Level linearity on the reference level range   | Pass   | 21: High Level Stability                          | Pass   |

The sound level meter submitted for testing has successfully completed the class 1 periodic tests of IEC 61672-3:2013, for the environmental conditions under which the tests were performed.

However, no general statement or conclusion can be made about conformance of the sound level meter to the full requirements of IEC 61672-1:2013 because evidence was not publicly available, from an independent testing organisation responsible for pattern approvals, to demonstrate that the model of sound level meter fully conformed to the requirements in IEC 61672-1:2013 and because the periodic tests of IEC 61672-3:2013 cover only a limited subset of the specifications in IEC 61672-1:2013.

| Uncertainties of Measurement - |         |                          |           |
|--------------------------------|---------|--------------------------|-----------|
| Acoustic Tests                 |         | Environmental Conditions |           |
| 125Hz                          | ±0.13dB | Temperature              | ±0.1°C    |
| 1kHz                           | ±0.13dB | Relative Humidity        | ±1.9%     |
| 8kHz                           | ±0.14dB | Barometric Pressure      | ±0.014kPa |
| Electrical Tests               | ±0.13dB |                          |           |

*All uncertainties are derived at the 95% confidence level with a coverage factor of 2.*



This calibration certificate is to be read in conjunction with the calibration test report.

Acoustic Research Labs Pty Ltd is NATA Accredited Laboratory Number 14172. Accredited for compliance with ISO/IEC 17025 - Calibration.

The results of the tests, calibrations and/or measurements included in this document are traceable to SI units.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports.

PAGE 1 OF 1



# CERTIFICATE OF CALIBRATION

CERTIFICATE No: **C37305**

EQUIPMENT TESTED : Sound Level Calibrator

**Manufacturer:** Svantek  
**Type No:** SV36      **Serial No:** 140737  
**Class:** 1  
**Owner:** EMM Consulting  
Level 3, 175 Scott Street  
Newcastle NSW 2300

**Tests Performed:** Measured Output Pressure level, Frequency & Distortion  
**Comments:** See Details and Class Tolerance overleaf.

## CONDITION OF TEST:

|                          |                      |                              |            |
|--------------------------|----------------------|------------------------------|------------|
| <b>Ambient Pressure</b>  | 1005 hPa $\pm 1$ hPa | <b>Date of Receipt :</b>     | 06/09/2023 |
| <b>Temperature</b>       | 24 °C $\pm 1$ ° C    | <b>Date of Calibration :</b> | 06/09/2023 |
| <b>Relative Humidity</b> | 35 % $\pm 5$ %       | <b>Date of Issue :</b>       | 06/09/2023 |

**Acu-Vib Test Procedure:** AVP02 (Calibrators)  
Test Method: AS IEC 60942 - 2017

**CHECKED BY:** .....

**AUTHORISED SIGNATURE:** .....



Helen See

Accredited for compliance with ISO/IEC 17025 - Calibration  
Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part.

The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



**WORLD RECOGNISED ACCREDITATION**  
Accredited Lab No. 9262  
Acoustic and Vibration  
Measurements

  
**Acu-Vib Electronics**  
CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory  
Unit 14, 22 Hudson Ave, Castle Hill NSW 2154  
(02) 9680 8133  
www.acu-vib.com.au

Page 1 of 2    Calibration Certificate  
AVCERT02.1    Rev.2.0    14.04.2021





**Acoustic  
Research  
Labs Pty Ltd**

Unit 36/14 Loyalty Rd  
North Rocks NSW AUSTRALIA 2151  
Ph: +61 2 9484 0800 A.B.N. 65 160 399 119  
www.acousticresearch.com.au

**Sound Calibrator**

IEC 60942:2017

**Calibration Certificate**

Calibration Number C23389

**Client Details** EMM Consulting  
Level 3, 175 Scott Street  
Newcastle NSW 2300

**Equipment Tested/ Model Number :** Pulsar Model 106  
**Instrument Serial Number :** 81334

**Atmospheric Conditions**

**Ambient Temperature :** 22.6°C  
**Relative Humidity :** 35.5%  
**Barometric Pressure :** 101.43kPa

**Calibration Technician :** Shaheen Boaz  
**Calibration Date :** 21 Jun 2023  
**Secondary Check:** Dhanush Bonu  
**Report Issue Date :** 21 Jun 2023

**Approved Signatory :** *Ken Williams* Ken Williams

| Characteristic Tested          | Result |
|--------------------------------|--------|
| Generated Sound Pressure Level | Pass   |
| Frequency Generated            | Pass   |
| Total Distortion               | Pass   |

| Nominal Level | Nominal Frequency | Measured Level | Measured Frequency |
|---------------|-------------------|----------------|--------------------|
| 94            | 1000              | 94.18          | 1000.30            |

The sound calibrator has been shown to conform to the class 2 requirements for periodic testing, described in Annex B of IEC 60942:2017 for the sound pressure level(s) and frequency(ies) stated, for the environmental conditions under which the tests were performed.

| Specific Tests | Uncertainties of Measurement - |                               |
|----------------|--------------------------------|-------------------------------|
|                | Environmental Conditions       |                               |
| Generated SPL  | ±0.10dB                        | Temperature ±0.1°C            |
| Frequency      | ±0.07%                         | Relative Humidity ±1.9%       |
| Distortion     | ±0.20%                         | Barometric Pressure ±0.014kPa |

All uncertainties are derived at the 95% confidence level with a coverage factor of 2.



This calibration certificate is to be read in conjunction with the calibration test report.

Acoustic Research Labs Pty Ltd is NATA Accredited Laboratory Number 14172.  
Accredited for compliance with ISO/IEC 17025 - Calibration.

The results of the tests, calibrations and/or measurements included in this document are traceable to SI units.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports.

## **Australia**

### **SYDNEY**

Ground floor 20 Chandos Street  
St Leonards NSW 2065  
T 02 9493 9500

### **NEWCASTLE**

Level 3 175 Scott Street  
Newcastle NSW 2300  
T 02 4907 4800

### **BRISBANE**

Level 1 87 Wickham Terrace  
Spring Hill QLD 4000  
T 07 3648 1200

### **CANBERRA**

Suite 2.04 Level 2  
15 London Circuit  
Canberra City ACT 2601

### **ADELAIDE**

Level 4 74 Pirie Street  
Adelaide SA 5000  
T 08 8232 2253

### **MELBOURNE**

Suite 8.03 Level 8  
454 Collins Street  
Melbourne VIC 3000  
T 03 9993 1900

### **PERTH**

Suite 9.02 Level 9  
109 St Georges Terrace  
Perth WA 6000  
T 08 6430 4800

## **Canada**

### **TORONTO**

2345 Yonge Street Suite 300  
Toronto ON M4P 2E5  
T 647 467 1605

### **VANCOUVER**

60 W 6th Ave  
Vancouver BC V5Y 1K1  
T 604 999 8297



[linkedin.com/company/emm-consulting-pty-limited](https://www.linkedin.com/company/emm-consulting-pty-limited)



[emmconsulting.com.au](http://emmconsulting.com.au)